

Polishing Fluid No. 10-2012

Technical Data Sheet

Page 1 of 1

Properties: AKEMI[®] Polishing Fluid No. 10-2012 is a rapid hardening product made

of highly efficient waxes and synthetic resins, dissolved in

trichloroethylene. Treated areas obtain a brilliant, anti-slippery surface

and the colour is intensified.

Application Area: AKEMI[®] Polishing Fluid No.10-2012 is suited for the care of floors,

staircases or window sills out of fine-ground or polished natural and cast stones, s.a. marble, granite, slate, terrazzo, travertine and similar for indoor use. The quality corresponds to the classic "edge finishing fluat".

Instructions for Use:

1. Clean the surfaces thoroughly with AKEMI[®] Stone Cleaner. They must be clean and absolutely dry before use of Polishing Fluid No. 10-2012. Ideal temperature for application 15-25°C.

2. Apply a thin layer with a cloth or brush, for larger areas apply with a

3. Repeat application on very absorbent, non-polished surfaces.

4. Polish surfaces with a soft cloth or a white nylon pad and a floor polishing machine when their appearance has become dull.

5. For regular cleaning use AKEMI® Mild Stone Soap.

Special Notes: - Use AKEMI[®] Liquid Glove to protect your hands.

- Objects in the working area which are not resistant to solvents, s.a. various synthetic materials, rubber, lacquered areas, must be

protected.

- At temperatures below 9°C the product becomes viscous, below 0°C it

becomes almost solid.

- Storage at a temperature of 15°C will render it ready to be worked

again.

- Apply the product in a thin layer, only, otherwise the surface will not

take a good polish.

- Films of polishing fluid can be removed by AKEMI® Wax Stripper.

- For adequate waste disposal container must be completely emptied.

Technical Data: Coverage: approx. 15 – 30 m²/liter

Colour: slightly yellowish
Density: approx. 0.75 g/cm³

Storage: 2 years if stored in cool place free from frost in its tightly closed original

container.

Health & Safety: Read Material Safety Data Sheet before handling or using this product.

Important Notice: The above information is based on the latest stage of development and

application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of

a sample piece.

TDS 11.15